



CaviBlaster 1222-E

Electric Motor 50/60 Hz, 12 gpm & 2,200 psi

Specifications and Options

This electric version of the 1222-G is compact, lightweight yet provides a superior cleaning performance utilizing the Ultra-Cavitation technology

Accessories Included:

Feed Pump with Hose Assembly (15 feet), By-Pass Hose (15 feet), Zero-thrust balanced Gun, High Pressure Hose (50 feet)

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections
Max. Pressure hose length recommended up to 300 ft (100 meters) total

SKID Dimensions

| | |
|-------------------|------------------|
| Length w/o handle | 35" / 89 cm |
| Length w handle | 45" / 114 cm |
| Width | 26" / 66 cm |
| Height | 29" / 74 cm |
| Weight | 465 Lbs / 211 Kg |

Pump System

| | |
|----------------------|-------------------------------|
| Pressure Pump | AR XWL 50.20 N |
| Pump Material / Type | Brass / Positive Displacement |
| Flow Rate | 13 gpm / 50 Lpm |
| Pressure | 2,200 psi / 152 Bar |
| Hose Diam/Max Lgth | 1/2" - 300 ft / 100 meters |

Shipping Dimensions

| | |
|------------------|----------------------|
| Pallet 40x48x36" | 500 Lbs Gross weight |
|------------------|----------------------|

* Pricing and specifications subject to change without notice

Drive System

| | |
|---------------------|------------------------|
| Motor | Multi-Voltage Electric |
| Enclosure | TEFC |
| Frame | 284T |
| Hertz | 50 Hz or 60 Hz |
| Voltage | 230-460 V |
| Phase | 3 Phase |
| Output HP/kW | 20 HP / 16 kW |
| Speed RPM USA/Intl. | 1,800 / 1,500 RPM |
| Starting System | Magnetic Start |

Ideal For

| |
|--|
| Small to Mid size Boat Hulls |
| Piers, Pilings & Seawalls |
| Running gear & Out drivers |
| Pools & Indoor Underwater Instalations |

Tool Options

| |
|--------------------------|
| Zero-Thrust Balanced Gun |
| Double Un-Balanced Guns |
| Single CaviDome |
| ROV Lance |

