

HYCON HH23 BREAKER

ANTI-VIBRATION HANDLES

HIGH PERFORMANCE



PRODUCT FEATURES

HYCON HH23 is a compact and sturdy breaker with 40 % higher performance than the HH20. It is designed for tough jobs in reinforced concrete, asphalt, ramming, etc.

The HYCON vibration-reduced handle is standard with the HH25, available in 20 and 30-lpm types.

HH23 is especially used by contractors, armies, asphalt companies, municipalities, etc., and is very suitable for the rental business. The standard tool size is hex 25 x 108 mm.

The breaker can be connected to the HPP series and other hydraulic power sources. Other tool sizes are available on request.

HYDRAULIC BREAKER HH23

	CE 20 lpm	CE 30 lpm
Item no.	1010023	1010123
Weight [kg / lbs]	23.4 / 51.5	23.5 / 51.8
Oil flow [LPM / GPM]	20 / 5	30 / 8
Working pressure [bar / psi]	120 / 1740	120 / 1740
Max pressure [bar / psi]	160 / 2320	160 / 2320
Tool shank HEX [mm] (optional)	25 x 108	25 x 108
Blow frequency [Hz]	1380	1380
Blow energy [joule]	85	95
Sound power level L _{Wa} [dB]	108	108
Vibration level, 3 axis [m/s ²]	8.0	8.0

ACCESSORIES

Dust suppression kit, item no. 3030051. HYCON water container item no. 1113286.

THE HYCON PRODUCT RANGE

CUT-OFF AND RING SAWS · CORE DRILLS · POST DRIVERS · PICK HAMMER · LIGHT & HEAVY DUTY BREAKERS
SUBMERSIBLE PUMPS · ROCK DRILLS · UNDERWATER EQUIPMENT · GASOLINE, DIESEL AND ELECTRIC POWER PACKS



HYCON A/S
Juelstrupparken 11
DK-9530 Støvring

Tel.: +45 9647 5200
Mail: hycon@hycon.dk
www.hycon.dk

DISTRIBUTOR: