

HYCON HH27 BREAKER

ANTI-VIBRATION HANDLES

HIGH PERFORMANCE



PRODUCT FEATURES

HYCON HH27 is exceptionally strong in coping with all jobs requiring extreme power (75 % higher performance than the HH20). It is designed for breaking reinforced concrete, asphalt, ramming jobs, etc. Best power-to-weight ratio.

HH27 comes as standard with the HYCON vibration-reduced

handle and is primarily used by contractors, armies, on railroads, etc. The standard tool size is hex 32 x 160 mm.

The breaker can be connected to the HYCON power packs and other hydraulic power sources. It is available both as 20 and 30-lpm types.

HYDRAULIC BREAKER HH27

	CE 28x152	CE 28x160	CE 32x152	CE 32x160
Item no.	1010527	1010427	1010127	1010027
Weight [kg / lbs]	27.4 / 60.4	27.4 / 60.4	27.4 / 60.4	27.4 / 60.4
Oil flow [LPM / GPM]	30 / 8	30 / 8	30 / 8	30 / 8
Working pressure [bar / psi]	130 / 1885	130 / 1885	130 / 1885	130 / 1885
Max pressure [bar / psi]	160 / 2320	160 / 2320	160 / 2320	160 / 2320
Tool shank HEX [mm] (optional)	28 x 152	28 x 160	32 x 152	32 x 160
Blow frequency [Hz]	1260	1260	1260	1260
Blow energy [joule]	105	105	105	105
Sound power level L _{Wa} [dB]	110	110	110	110
Vibration level, 3 axis [m/s ²]	10.7	10.7	10.7	10.7

ACCESSORIES

Dust suppression kit, item no. 3030051. HYCON water container item no. 1113286.

THE HYCON PRODUCT RANGE

CUT-OFF AND RING SAWS · CORE DRILLS · POST DRIVERS · PICK HAMMER · LIGHT & HEAVY DUTY BREAKERS
SUBMERSIBLE PUMPS · ROCK DRILLS · UNDERWATER EQUIPMENT · GASOLINE, DIESEL AND ELECTRIC POWER PACKS



HYCON A/S
Juelstrupparken 11
DK-9530 Støvring

Tel.: +45 9647 5200
Mail: hycon@hycon.dk
www.hycon.dk

DISTRIBUTOR: